

RF SPEC.

Frequency Range	Insertion Loss	VSWR	Isolation	Power Handling
DC-6GHZ	<0.30dB	<1.30	>70dB	30W
6-12.4GHZ	<0.40dB	<1.40	>65dB	20W
12.4-18GHZ	<0.50dB	<1.50	>60dB	15W
18-26.5GHZ	<0.60dB	<1.60	>55dB	10W



Characteristics	Outline Drawing (mm)
RF Impedance: 50 ohm	
Control Voltage/Current: DC12V /300mA DC24V / 150mA	
Switching Time: <20ms	
Operating Life: >100,000	
Operating Temperature: -25 ~ +65 °C	
RF Interface: K(2.92mm) female	
Weight:	

Schematics	
<p>Voltage Control</p>	<p>With TTL Logic Control</p>

Part Number Selector

Series	RF Channel	Voltage	Frequency Range	TTL Control	Option
P/N: 1K	<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>	-V (Anti Vibration)
	<input type="checkbox"/> 9	<input type="checkbox"/> 1 <input type="checkbox"/> 2 DC12V	<input type="checkbox"/> 2 <input type="checkbox"/> 6 DC-26.5GHZ	<input type="checkbox"/> NO TTL	-W (Splash)
	<input type="checkbox"/> 10	<input type="checkbox"/> 2 <input type="checkbox"/> 4 DC24V		<input type="checkbox"/> T TTL	

- 1K101226 (SP10T Normally Open Type/DC12V/DC-26.5GHZ/K female/DB15 male)
- 1K92426 (SP9T Normally Open Type/DC24V/DC-26.5GHZ/K female/DB15 male)
- 1K102426T (SP10T Normally Open Type/DC24V/DC-26.5GHZ/K female/DB15 male)

