

P/N:T8-USB DC-18GHZ With Termination

P/N:T8K-USB DC-40GHZ With Termination



USB Controlled With Computer

Features

- . SP8T RF Electromechanical Switches With Internal Terminations
- . Small Size 108x63.5x63.5mm
- . Broadband RF Frequency Range:DC-18GHZ / DC-40GHZ
- . USB Remote Controlled
- . Operating in Windows 32/64 Bit System
- . Configurable into SPST,SP2T,SP3T,SP4T,SP5T,SP6T,SP7T,SP8T etc.
- . Local LED Indicator For RF Patch

Applications:

- . ATE System
- . EMC testing
- . Lab and RF Control equipment
- . Test for WLAN,WIFI,LTE and Wireless System

RF SPEC.

Frequency Range	DC-3GHZ	3-6GHZ	6-12.4GHZ	12.4-18GHZ
VSWR	<1.20	<1.30	<1.40	<1.50
Insertion Loss	<0.2dB	<0.3dB	<0.40dB	<0.60dB
Isolation	>80dB	>70dB	>65dB	>60dB
*Power Handing(CW)	60W	40W	20W	10W
Terminations Power Handing(CW)	1W			

Frequency Range	DC-6GHZ	6-12.4GHZ	12.4-18GHZ	18-26.5GHZ	26.5-40GHZ
VSWR	<1.25	<1.35	<1.50	<1.60	<1.90
Insertion Loss	<0.2dB	<0.3dB	<0.50dB	<0.80dB	<1.0dB
Isolation	>70dB	>65dB	>60dB	>55dB	>50dB
*Power Handing(CW)	30W	20W	15W	10W	5W
Terminations Power Handing(CW)	1W				

- . RF Impedance: 50 ohm
- . RF Interface:SMA / K(2.92mm) female
- . Switching Time: <40ms
- . Life:>100, 0000 cycles
- . Switching Sequence:Break Before Make
- . Operating Temperature: -20 ~ +50°C
- . Power Supply:DC12V/4W



Accessories:

- . T8-USB OR T8K-USB Case
- . USB Cable Length=1.5m
- . AC/DC12V Power Adaptors
- . Remot Controlled Software

SIZE

