

RF SPEC.

Frequency Range	Insertion Loss	VSWR	Isolation	Power Handling
DC-6GHZ	<0.30dB	<1.30	>70dB	30W
6-12.4GHZ	<0.40dB	<1.40	>65dB	20W
12.4-18GHZ	<0.50dB	<1.50	>60dB	15W
18-26.5GHZ	<0.70dB	<1.60	>55dB	10W
26.5-40GHZ	<0.90dB	<1.80	>50dB	5W
40-50GHZ	<1.20dB	<1.90	>50dB	3W
50-67GHZ	<1.80dB*	<2.00**	>50dB	2W

Internal Termination: 1W

*MAX <2.0dB **MAX <2.20

Characteristics	Outline Drawing (mm)
RF Impedance 50 ohm Control Voltage/Current: DC12V/200mA, Reset=N*200mA DC24V/100mA, RESET=N*100mA Switching Time <20ms Operating Life >100,0000 Operating Temperature -25 ~ +65°C RF Interface 1.85mm female	Dimensions: 7.5, 55.0, 4.5, 8.5, 63.5, 53.3, 4-Ø3.2, 63.5, 53.3, 9-1.85mm female Diameter=39mm, 8-50ohm Internal Terminations. Label: D-sub 15pins male

Voltage Control	With TTL Logic Control

Part Number Selector

Series	RF Channel	Control Voltage	Frequency Range	Voltage Polarity	TTL Control	Indicator	Control Interface	Option
L1TW	8	☐ ☐	☐ ☐	☐ ☐	☐ ☐	☐ ☐	☐ ☐	☐ ☐
		12 DC12V	53 DC-53GHZ	Negative	NO TTL	No Indicator	Solder Pin	Anti Vibration
		24 DC24V	67 DC-67GHZ	Positive	With TTL	With Indicator	DB male	Splash
					T-S	With TTL & Self cut off Circuits		

* NO COM Port Polar SPEC. For With TTL Control

L1TW81267 (SP8T Latching Type With Termination/DC12V(COM Port is Negative, RESET is Positive)/DC-67GHZ/1.85mm female/DB15 male)

L1TW82467R (SP8T Latching Type With Termination/DC24V(COM Port is Positive, RESET is Negative)/DC-67GHZ/1.85mm female/DB15 male)

L1TW82467T-S (SP8T Latching Type With Termination/DC24V/DC-67GHZ/With TTL Control & self cut-off circuits/1.85mm female/DB15 male)



Tel :0086-10-82087227

Fax:0086-10-82087380

E-mail: sales@rf-switch.com

Web site: www.rf-switch.com